



MINI-CC



E' una "MINI CALIBRATRICE CIRCOLARE" con ampie possibilità di impiego.

La versatilità, l'economicità ed il minimo ingombro della "MINI-CC", la rendono particolarmente apprezzata, sia dal piccolo che dal grande produttore.

La "MINI-CC" può lavorare con facilità, qualsiasi tipo di orto-frutta, che abbia diametri abbastanza regolari, eseguendone la calibratura, con un dispositivo di pesatura elettronica.

La "MINI-CC" può essere equipaggiata con due diversi tipi di carrellini portafrutti (passo 76 o passo 89) e, può essere utilizzata come:

- a) Mini calibratrice circolare
- b) Campionatrice per il controllo della merce in entrata al magazzino
- c) Confezionatrice semiautomatica per cestini da gr500, gr1000, gr2000, ecc.. ecc..

It is an "ENDLESS MINI SIZER" with ample possibilities for use.


The versatility, inexpensiveness and minimum overall dimensions of "MINI-CC" make it particularly valuable for both small and large producers.

"MINI-CC" can easily process any type of vegetable and fruit having rather regular diameters, reading their size by an electronic weighing device.


"MINI-CC" can be equipped with two different types of fruit-holder carriers: (pitch 76 or pitch 89) and may be used as:

- a) Endless mini-sizer
- b) Sampling unit for goods check-up on entering the warehouse
- c) Semiautomatic packaging unit for 500g-1000-2000g baskets etc.

| CARATTERISTICHE MINI-CC MINI-CC FEATURES | PASSO 76mm 76mm PITCH | PASSO 89mm 89mm PITCH |
|---|-------------------------------|-------------------------------|
| CARRELLINI PORTA FRUTTI FRUIT-HOLDER CARRIERS | 48 | 40 |
| VELOCITA' MASSIMA MAXIMUM SPEED | 9 FRUTTI/SEC. 9 FRUITS/SEC | 8 FRUTTI/SEC. 8 FRUITS/SEC |
| PESO MINIMO MINIMUM WEIGHT | 25 g | 30 g |
| PESO MASSIMO MAXIMUM WEIGHT | 300 g | 450 g |
| DIAMETRO MINIMO MINIMUM DIAMETER | 35 mm | 40 mm |
| DIAMETRO MASSIMO MAXIMUM DIAMETER | 80 mm | 100 mm |
| PRECISIONE ACCURACY | + -2 g | + -2 g |
| USCITE TOTALI TOTAL EXITS | 6 | 6 |
| USCITE CON ELETTROMAGNETE EXITS W/ELECTROMAGNET | 5 | 5 |
| NUMERO DI PROGRAMMAZIONI MASSIME MAXIMUM NUMBER OF PROGRAMMING | 9 | 9 |
| PROGRAMMAZIONE PROGRAMMING | DISPLAY | DISPLAY |
| NUMERO DI CALIBRAZIONI MASSIME MAXIMUM NUMBER OF SIZING | 12 | 12 |



ROTAZIONE ANTIORARIA
COUNTERCLOCKWISE ROTATION



ROTAZIONE ORARIA
CLOCKWISE ROTATION

